

A9



Watch the video on youtube:
www.youtube.com/fasavideo

Technical data:	A9 50T	A9 55T	A9 66T
Code	8.516.0413	8.516.0414	8.516.0424
power supply	24 V DC	24 V DC	24 V DC
scrubbing width	500 mm	550 mm	660 mm
squeegee width	800 mm	800 mm	800 mm
max working capacity	2250 m ² /h	2475 m ² /h	2970 m ² /h
detergent tank capacity	67 l	67 l	67 l
recovery tank capacity	77/95 l	77/95 l	77/95 l
traction	200W/automatic	200W/automatic	200W/automatic
vacuum motor	450W	450W	450W

Standard equipment



- A9 50T**
- 5.511.1097
PPL brush Ø 483 mm - 19"



- A9 55T**
- 2 x 5.511.1101
PPL brush Ø 275 mm - 10"



- A9 66T**
- 2 x 5.511.1105
PPL brush Ø 330 mm - 13"



- 4.508.X468
Front squeegee blade L.830 mm
Shore 40 Th. 2.5 mm
- 4.508.X467
Rear squeegee blade L.870 mm
Shore 40 Th. 3 mm

A9

- Suitable to work for the maintenance and deep cleaning of large areas (up to 2.200 m²)
- User friendly control panel: forward speed setting, scrubbing and vacuuming selectors, battery charge indicator, traction direction indicator, key main switch
- Large handle with traction driving lever for forward and backward directions
- Self levelling brush plate
- Cover removable without tools provided with self locking system
- Quick vacuum motor and filter inspection, without tools
- Detergent solution tank with large opening protected by quick locking cap
- Parking brake directly on the wheel
- Non-marking wheels
- Easy squeegee regulation without tools
- Movable shock-proof squeegee
- Hour meter and solenoid valve.

Walk-behind floor scrubber driers



User friendly control panel. Speed adjustment selectors. General ON/OFF and key switch, brush and vacuum motor switch. Thermal circuit breaker to protect vacuum motor and brush motor, battery level control, hour meter.

Easy access to battery and vacuum motor compartment, without using tools. Large tank capacity, at the top in the category (67 l). 2 x 12V -118 Ah C5 batteries to grant long work autonomy, up to 3 hours.



Control lever for brush operation and detergent water outflow. Recovery tank drain hose. Quick fitting battery charger plug.

Heavy duty 15 mm steel monobloc brush plate. Great pressure on the floor for a deep cleaning even on the toughest dirt. Self levelling system. Solenoid valve to stop the detergent water outflow during the work interruptions.



Optional accessories:



- 2 x 0.107.0002
Tubular battery Pb-acid
12V 118Ah C5



- 2 x 0.107.0063
GEL Battery 12 MFP 105
12V 105Ah C5



- 0.108.0001
Battery Charger 24V 25A
220-240/50-60


- 5.511.1494
On-board Battery charger
kit - 24V - 12A



- 4.508.1178 Polyurethane
front blade L.830 TH. 3
- 4.508.1177 Polyurethane
rear blade L.870 TH. 4



- 5.511.1098
Tynex brush Ø 483 mm-19"
- 5.511.1102
Tynex brush Ø 275 mm-10"
- 5.511.1106
Tynex brush Ø 330 mm-13"
- 5.511.1128
PPL 0,03 brush Ø 483 mm-19"
- 5.511.1254
PPL 0,03 brush Ø 275 mm-10"
- 5.511.1255
PPL 0,03 brush Ø 330 mm-13"
- 5.511.1206
PES brush Ø 483 mm - 19"
- 5.511.1201
PES brush Ø 275 mm-10"
- 5.511.1202
PES brush Ø 330 mm-13"



- 5.511.1099
EWU pad driver Ø 483mm-19"
- 5.511.1103
EWU pad driver Ø 275mm-10"
- 5.511.1107
EWU pad driver Ø 330mm-13"



- (5 pcs package)
- 6.508.0034 - Ø 483 mm-19"- beige
- 6.508.0041 - Ø 483 mm-19"- green
- 6.508.0048 - Ø 483 mm-19"- black
- 6.508.0095 - Ø 280 mm-11"- beige
- 6.508.0096 - Ø 280 mm-11"- green
- 6.508.0097 - Ø 280 mm-11"- black
- 6.508.0030 - Ø 340 mm-13"- beige
- 6.508.0037 - Ø 340 mm-13"- green
- 6.508.0044 - Ø 340 mm-13"- black