


Hot water high-pressure cleaners

Sundek 5Y LP



Standard equipment:



Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling (three phase models)
- Three ceramic coated pistons, brass linear pump head (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve
- Vertical burner with high thermal efficiency steel coil.
- Suction and delivery S/S valves. • Safety valve • Temperature regulation gauge • Glycerine pressure gauge. • Automatic Stop System late shut down protection 24V. • Adjustable detergent delivery with built-in tank for indirect suction. • Auxiliary motor for burner air-cooling • Two ways fuel pump • Low fuel lamp • Ergonomic handles and impact resistant covers • Accessory holder
- Power cable (m 5).

Optional:

- Hose-reel with brake code 6.608.0077
- Antiscale LC-PRECAL (pcs. 4 x 5 lt.) code 3.697.0044

	Sundek 5Y 1311 LP	Sundek 5Y 1515 LP	Sundek 5Y 2015 LP
Code	8.621.2948	8.621.2942	8.621.2943
Operat. pressure bar	30 ÷ 110	30 ÷ 150	30 ÷ 200
Operat. pressure psi	1595	2175	2900
Delivery rate l/h	330 ÷ 660	450 ÷ 900	450 ÷ 900
Temp. max	140°C	140°C	140°C
Power ass. W	3000	5500	7300
RPM	1450	1450	1450
Voltage	230 V~50 Hz	400 V~50 Hz	400 V~50 Hz